NEW EUROCARGO E5



PEKFECI IN EVENI SIIUMIIUM



EUROCARGO.

PERFECT IN EVERY SITUATION.

Eurocargo is the segment's trail-blazer, with a higher mileage behind it than any competitor. And it's still a benchmark of reliability and flexibility, that's designed and built to last.

Now, on the strength of its exclusive HI-eSCR technology, Eurocargo has set another record by combining the highest levels of innovation, with first-rate performance and optimised fuel-efficiency.

Versatility is the keyword in the ever more competitive and continually changing world of work. The Eurocargo range is the most comprehensive in its class, bar none. With 14 gross vehicle weight variants, 7 power ratings, 13 gearboxes, 15 wheelbases and 3 cab types, Eurocargo is available in over 11,000 permutations, to meet your every need, however specific.

The new Tector 5- and 7-litre Euro VI engines are the only power-plants in their class to mount SCR technology, and are designed for high efficiency, light weight and improved performance. Equally suitable for town centres, combined-cycle driving and the most demanding long-haul work, they offer excellent performance with power ratings of up to 320 HP and torque of up to 1,100 Nm. Another new development, on top of the HI-eSCR system, is the new Eurotronic 12-speed automated gearbox, which is also available for trailer versions.

Eurocargo's driving style puts safety and stability first, thanks to the new ESP fitted as standard on 12- to 19-tonne versions. And the new Eurocargo Euro VI is even more adaptable to

countless types of conversion, and even easier to maintain.



N E W EUROCARGO





engine speeds delivers a smooth ride, fewer gear changes, less engine wear and better energy efficiency. This helps meet the needs of even the most demanding customers, and makes Eurocargo a new benchmark in its class.

Eurocargo's diesel engines are turbocharged **Common Rail** units with waste-gate, and come in two displacements (4.5-litre 4-cylinder and 6.7-litre 6-cylinder) and **seven power ratings** (from 160 to 320 HP, with maximum torque of 580 to 1,100 Nm). Peak efficiency is reached with the «Top Power» 4-cylinder, 210 HP engine, with maximum torque of 750 Nm. This represents the ideal solution for a market segment which, under Euro V, was covered by the 6-cylinder, 220 HP engine, and which can now benefit from the lower fuel consumption and lower weight of a 4-cylinder engine without compromising on performance and with an increase in maximum torque.

Thanks to the increased torque and power of the new engines, the new Eurocargo Euro VI range can handle increased trailer weights too. For 8- to 12-tonne versions, trailer weight rises from 16,500 kg to 18,000 kg, even with a 6-speed automated gearbox; and for versions over 15 tonnes, it increases from 32,500 kg to 35,000 kg.

EURO VI ENGINES	N. CYLINDERS	DISPLACEMENT	POWER	MAX TORQUE
			18 Kw (160 HP) to 2500 Rpm	580 Nm from 1250 to 1950 Rpm
TECTOR 5	4 IN LINE	4.5 LITRES	137 Kw (190 HP) to 2500 Rpm	680 Nm from 1250 to 1900 Rpm
			152 Kw (210 HP) to 2500 Rpm	750 Nm from 1400 to 1800 Rpm
			162 Kw (220 HP) to 2500 Rpm	800 Nm from 1250 to 1900 Rpm
TECTOR 7	6 IN LINE	6.7 LITRES	185 Kw (250 HP) to 2500 Rpm	850 Nm from 1250 to 2050 Rpm
TECTOR /	O IIV LIIVE	6,7 LITNES	206 Kw (280 HP) to 2500 Rpm	1000 Nm from 1250 to 1950 Rpm
			235 Kw (320 HP) to 2500 Rpm	1100 Nm from 1250 to 1900 Rpm

EURO VI ENGINES AND PERFORMANCE


On board the New Eurocargo Euro VI, the real innovation is IVECO's technological know-how. The new Tector 5 and Tector 7 engines have two key strengths at their disposal: flexibility and HI-eSCR technology.


The HI-eSCR catalytic reduction system, covered by an FPT INDUSTRIAL patent, enables Eurocargo to meet Euro VI limits without recourse to EGR (exhaust gas recirculation). This is one of the new features that set Eurocargo apart from its competitors: a single emissions abatement system that does not affect the combustion process, does not require an auxiliary cooling system and does not impose constraints on vehicle architecture or costs. All of this translates into fuel consumption in line with Euro V, and improved performance compared with the previous-generation engines. The new technology represents a significant innovation with zero impact on engine architecture. What's more, the consistently high torque values over a broad band of


HI-eSCR






































VERSATILITY

For every cargo, there's a Eurocargo.

The Eurocargo range is the most extensive in its class:

- **14 gross vehicle weight variants** (from 7.5 to 18 tonnes)
- **7 power ratings** (from 160 to 320 HP)
- 13 gearboxes (six manual, four automated and three automatic)
- 4x2 and 4x4 drive
- **14 wheelbases** (from 3,105 to 6,570 mm)
- **4** 3 types of cab with 2 roof heights.

If you multiply the number of variants by all the suspension, axle and final-drive ratios available to suit specific applications, you reach the incredible total of over II,000 permutations, all with the guarantee of IVECO know-how, technologies and manufacturing processes.

Eurocargo's outstanding adaptability to every requirement means that you'll always find the right conversion for your mission. The range of possible conversions includes box vans and curtain-siders for **high load capacity**, temperature-controlled boxes and three-way tippers for **ease of conversion**, tankers and mobile shops for **agility and compact size**, lift platforms, high-access platforms, fire and rescue conversions, compact concrete mixers and sweepers for cleaning and maintenance services

The vast range of transmissions and final-drive ratios makes Eurocargo **suitable for every work challenge,** terrain and conversion, with long gearing for motorway runs and short ratios for heavy-duty work and on difficult surfaces (construction sites, unmetalled tracks, mountain roads).

To facilitate and simplify connection between vehicle and conversion, you can specify an optional expansion module ECU and CAN-open interface. The latter can transmit over 300 analogue and digital input and output signals.

The parallel 'C' Section chassis frame in high-yield-strength steel is free from obstructions on top and can accommodate body lengths of between 4,265 and 10,175 mm. The equidistant holes drilled in the sidemember optimise the time and cost of fitting superstructures and machinery, without compromising the corrosion treatment of the frame. Eurocargo also offers an extensive range of electro-actuated power take-offs with maximum torque delivery of up to 1,000 Nm.

The flexibility of Eurocargo, carefully balanced with structural strength, gives it unbeatable driveability wherever you go:

• In city centres, it's outstandingly agile thanks to its cab width of just 2.10 metres, steering angle of 52 degrees and tight turning circle (less than 12 metres with a 3105 mm wheelbase).

In combined-cycle and motorway driving, it's stable and secure even in the event of unexpected manoeuvres, while the power and flexibility of its engines ensure high commercial speeds.

On demanding road surfaces or in extreme climates, it's ready for anything thanks to the natural, stress-free handling afforded by its exceptionally robust structure and class-leading safety equipment.

CABS

MLC - SHORT, LOW ROOF

MLL - LONG, HIGH ROOF







CAB WITH I STEP

CAB WITH 2 STEPS

CAB WITH I STEP

CAB WITH 2 STEPS

MLL - LONG, LOW ROOF

MLD - DOUBLE



+ + +







CAB WITH I STEP

CAB WITH 2 STEPS

CAB WITH I STEP

CAB WITH 2 STEPS



THE RANGE





CAB WITH I ACCESS STEP, 6 TO 12 TONNES

				VERSION		CABS			ENGINES							GE	EARBOXE	S	S	USPENSIO	NS	WHEEL BASES
MODEL	GVW	MAX GCW								TECTOR 5			TECTOR 7		Ma	nual	Automated	Automatic				WHEELBASES
110011	(KG)	(KG)	Std	R (Dowing version)	K (Tipper)	Short	Long	Double	160 HP	190 HP	210 HP	250 HP	280 HP	320 HP	5 6	9	6	5	Mechanical	Pneumatic rear	Full pneumatic	(MM)
65E	7000		•		•	•	•		•						•		•		•	•		3105-3330-3690-4185-4455-4815
75E	7500		•	•	•	•	•		•	•	•				•		•	•	•	•		3105-3330-3690-4185-4455-4815
80EL	8000	16500	•	•	•	•	•		•	•	•				•		•	•	•	•		3105-3330-3690-4185-4815
80E	8000		•	•	•	•	•	•		•	•				•	•	•	•	•	•	•	3105-3330-3690-4185-4455-4815
90E	9000	18000	•	•	•	•	•	•		•	•				•	•	•	•	•	•	•	3105-3330-3690-4185-4455-4815
100E	10000		•	•	•	•	•	•		•	•				•	•	•	•	•	•	•	3105-3330-3690-4185-4455-4815
I I OEL	11000	18000	•	•		•	•			•	•				•	•	•	•	•	•		3105-3330-3690-4185-4455-4815
I 20EL	12000	15500	•	•		•	•	•		•	•					•	•	•	•	•		3105-3330-3690-4185-4455-4815





CAB WITH 2 ACCESS STEPS, 12 TO 19 TONNES

				VERSION		CABS			ENGINES							G	EARB	OXES	S	USPENSIC	ONS	WHIEL BACEC
MODEL	GVW	MAX GCW								TECTOR 5		TECTOR 7		Manual		Autom	ted Automatic				WHEELBASES	
110022	(KG)	(KG)	Std	R (Dowing version)	(Tipper)	Short	Long	Double	160 HP	190 HP	210 HP	250 HP	280 HP	320 HP	6	9	6	12 5	Mechanical	Pneumatic rear	Full pneumatic	(MM)
120E	12000	26000	•	•	•	•	•	•		•	•	•	•		•	•	•	• •	•	•	•	3105-3690-4185-4455-4815-5175-5670-6570
140E	14000	26000	•	•	•	•	•	•		•	•	•	•		•	•	•	•	•	•	•	3105-3690-4185-4455-4815-5175-5670-6570
150E	15000	35000	•	•	•	•	•	•		•	•	•	•	•	•	•	•	• •	•	•	•	3105-3690-4185-4455-4815-5175-5670-6570
160E	16000	33000	•	•	•	•	•			•	•	•	•	•	•	•	•	•	•	•		3105-3690-4185-4455-4815-5175-5670-6570
180E	18000	35000	•	•	•	•	•					•	•	•	•	•	•	• •	•	•		3690-4185-4590-4815-5175-5670-6210-6570





4x4 WITH 2 ACCESS STEPS, II.5 TO I5 TONNES

				VERSION			CABS					ENGINES	I .			GEAR	RBOXES	SUSPEN	ISIONS	WHIEL BACEC
MODEL	GVW	MAX GCW	AX GCW							TECTOR 5			TECT	OR 7		М	lanual			WHEELBASES
MODEL	(KG)	(KG)	Std	R (Dowing version)	K (Tipper)	Short	Long	Double	160 HP	190 HP	210 HP	220 HP	250 HP	280 HP	320 HP	6	6+PTO	Parabolic	Reinforced	(MM)
I I OE	11500	21000	•	•	•	•	•					•	•			•	•	•	•	3240-3690-3915-4150
150E	15000	24000	•	•	•	•	•						•	•		•	•	•	•	3240-3690-3915-4150













VERSATILITY

EUROCARGO 4x4

MODEL		TV	EELS VIN 22.5	•		WHI SIN 865/8	GLE			TV	EELS /IN 22.5			WHE SIN 95/8				WHE SING 14F	GLE	
Wheelbase (mm)	3240	3690	3915	4150	3240	3690	3915	4150	3240	3690	3915	4150	3240	3690	3915	4150	3240	3690	3915	4150
Ramp breakover angle (degrees)	21	19	18	18	22	20	19	19	21	19	18	18	22	22	21	21	23	23	22	22
Departure angle (degrees)	15	15	15	П	17	17	17	12	16	16	16	11	16	16	16	12	17	17	17	13
Approach angle (degrees)		2	28			2	.9		28				31				32			
Ground clearance		3	21			3.	51			3	37			392				428		
Lateral gradient (degrees)		3	30			2	.8		30					2	.8			2	26	
Maximum climbable gradient ON ROAD		4	1%			38	3%		38%					33	3%			3	1%	
Maximum climbable gradient OFF ROAD		>	00%			> (00%			> (00%			>8	0%			>7	4%	
Wading depth up to (mm)		4	73			5(01			4	89			54	42			5	78	

With Eurocargo 4x4, strength knows no limits.

Designed for the most demanding off-road work, Eurocargo 4x4 incorporates a specific series of solutions for protecting its structure: **steel bumpers**, retractable access steps and a **specific radiator guard**. Available with a day or sleeper cab with standard roof, it has a gross vehicle weight of 11.5 or 15 tonnes and a range of wheelbases measuring from 3,240 to 4,150 mm.

Eurocargo 4x4 mounts a Tector 7 engine in 220 and 250 HP variants on the 11.5 tonne version, and 250 and 280 HP variants on the 15 tonne version. The ZF six-speed manual gearboxes are fitted with a **servoshift system** for easy gear-changing even in the most demanding work conditions.

Permanent four-wheel drive is provided by a longitudinal differential, which distributes torque between the front and rear axles. What's more, you can select a fast or slow distributor ratio, according to conditions (on / off road). All the differentials are equipped with a manually operated locking system to ensure traction even in especially adverse, low-grip conditions. Eurocargo 4x4 is fitted with a double-reduction rear axle and is available in versions **with single or twin wheels.** Braking comes courtesy of simplex drum brakes on the rear axle and duplex drums up front, while you can specify either parabolic or semi-elliptical leaf spring suspension.

Eurocargo 4x4 is at home anywhere. The outstandingly low emissions of the engines and the excellent steering angle (from 40° to 48° depending on tyres) enable you to use it on urban construction sites too.











DESIGN

It's clear at first sight that Eurocargo is a solid, dynamic, modern

vehicle, with an unmistakeable shape and strong character. The front features an **imposing grille** equipped with non-slip steps for washing the windscreen, a bumper with built-in light clusters (grouped together for ease of maintenance) and a large space for your company's logo above the IVECO badge. The bumpers and mudguards are also available in the same colour as the body. And if you're buying your vehicle for off-road work, you can specify a one-piece steel bumper. Both sides of the sleeper cab feature remote electric hatch releases that give access to two illuminated storage boxes (with total capacity of 260 litres) even from the outside. Cab access is aided by **large handles** and **non-slip steps** for getting in and out easily and without risk. And six rear-view mirrors ensure maximum visibility in all directions.











Lefthand drive image for illustrative purposes only



COMFORT

Designed around driver comfort.

Climb into a Eurocargo cab, and you'll see that everything is clear, simple and in easy reach. The layout of the functions is simple and intuitive, with all the instruments directly in front of the driver, and all the controls in the steering wheel area. All the most frequently used buttons are grouped together on the dashboard in the most accessible positions, for maximum safety.

The gear stick is built into the compact, linear dashboard, making it quicker and easier to cross from one side of the cab to the other (essential for urban work).

The power take-offs are managed by an ECU (Expansion Module), which is operated electrically by the driver by means of a dash-mounted switch.

The new instrument panel features new graphics for displaying a wide range of useful data, so that you can keep a constant eye on all key vehicle and route parameters, such as fuel level, average and real-time fuel consumption, service deadlines, travelling times and average speed.

For top-level on-board entertainment, a new Bluetooth® radio is available, complete with:

- Microphone built into the front control panel
- USB interface / Aux-IN socket
- CD, Mp3, WMA and digital format player
- iPod and iPhone compatible, "Made for Apple" certified.

For maximum quality of life on board on every job, Eurocargo is available with 3 different types of cab:

- day, for distribution and short-haul work or when body length is a priority;
- sleeper with standard or high roof, for long-haul work and jobs involving overnight stops;
- double, with room on board for 6 passengers plus driver (ideal for getting work-crews to construction sites).

In all cabs, the heating and ventilation system means you can get the cab temperature you want, quickly and with optimum air distribution. A manually controlled air conditioning system and programmable supplementary heater are also available as options.

Eurocargo's seats feature integral head-restraints and seat belts, and are optionally available with air suspension. **Upholstered in cloth or imitation leather,** they ensure the highest levels of strength and practicality.



COMFORT

The sleeper cab is equipped with I or 2 bunks (an extra-size single bunk is available as an option) and can be fitted with a fridge or insulated cool-box.

On day-cab versions with double passenger seat, the central back-rest can be folded completely flat to provide a table with cup-holder and cubby hole.

The sleeping area features an adjustable lamp and a **"bed module",** for controlling the lighting and climate control, and opening and closing the doors, windows and skylight directly from the bunk.















Lefthand drive images for illustrative purposes only

28



When it comes to commercial vehicles, safety means a lot of things: safety for the people on board, for other road-users and pedestrians, for the vehicle's cargo and for the value of your investment.

IVECO has a multiple approach to safety:

- on the **passive safety** front, its cabs provide effective protection in the event of
- on the active safety front, Eurocargo offers class-leading road-holding and braking
- and in terms of **preventive safety**, the driver-centred cab reduces fatigue and

Latest-generation electronic systems also make a major contribution to safety, including the new enhanced stability control system (EVSC) available as an option on 7.5- to 10-tonne versions, and as standard on 11- to 18-tonne versions.





EVSC

Control

In the event of oversteer, you release the brake pedal. understeer or sudden changes in trajectory, it modulates the engine braking and brakes each wheel individually so as to stabilise the vehicle.

HILL HOLDER

Enhanced Vehicle Stability During hill-starts, Hill Holder prevents the vehicle from rolling backwards for a few seconds after





RELIABILITY

Changing gear can have a major effect on vehicle performance and fuel

consumption. Eurocargo has the answer in the form of highly flexible engines, which minimise the need to change gear, and an increasing range of automated transmissions. To meet the needs of every application as effectively as possible, Eurocargo is available with ZF 5-, 6- and 9-speed manual transmissions; ZF 6- and 12-speed automated transmissions, and Allison automatic transmissions.

Allison automatic transmissions, with torque converter, are available on the entire 4x2 range, and offer unbeatable comfort for city use, where "stop & go" work is par for the course: since urban work involves about 1,200 gear changes a day, you can see how much stress and energy an auto box saves for the driver.




Substantial investments have been made in automated transmissions, with the result that you can now specify a 6-speed automated transmission or the new **Eurotronic** 12-speed automated transmission, on all 6-cylinder Tector 7 engines on 12- to 19-tonne versions, including for trailer versions.





RELIABILITY

Eurocargo's reliability is also backed up by the evolution of the Tector engines. HI-eSCR technology improves performance and engine life. The new throttle valve on the exhaust line helps bring the system up to emissions abatement temperature and optimum HI-eSCR operating conditions more quickly. The increased power of the Euro VI engines is accompanied by enhanced efficiency of the engine braking.



To ensure long, trouble-free service-life, Eurocargo uses an outstandingly strong rolled frame, with the mechanical qualities you'd expect from a heavy vehicle, but lower tare weight.

Thanks to its **chassis frames with C-section sidemembers in high-yield-strength steel** (Fe420), it can readily withstand the stresses generated by an unbalanced load or sudden change of trajectory.

To enhance the long-term protection of metal surfaces, certain components have been improved, and anti-abrasion and anti-corrosion treatments with Tectyl are available as an option.

Eurocargo is available with **parabolic, reinforced parabolic or semi-elliptical** suspension, or **rear-air or full-air suspension** (with 2 bellows for the 7.5-to 14-tonne versions and 4 bellows for the 15- to 18-tonne versions) **with ECAS** system (Electronically-Controlled Air Suspension). ECAS ensures high levels of comfort at the wheel, and constant suspension geometry regardless of speed, load and type of road surface.

Developed on the strength of IVECO's long experience in heavy haulage, quarry and construction vehicles, **the front and rear axles and braking system** ensure high **reliability** and consistent performance over time. All 4x2 versions have **disc brakes on both axles.**


The braking system is air-hidraulic on the 7.5- to 10-tonne range and full air on the 11- to 18-tonne range. With the availability of a wide range of options, vehicle configurations can be tailored to your specific applications and most frequently used routes, thus ensuring safety and comfort in all surface conditions. The entire Eurocargo range, with Tector 5 and Tector 7, is equipped with a standard engine brake. You can also select engine-brake operating mode by means of a lever on the right of the steering column.

	MECHA	NICAL SUSP	ENSION	AIR SUSPENSION						
MODEL	PARABOLIC	REINFORCED PARABOLIC	SEMI-ELLIPTICAL LEAF SPRING	/P (REAR ONLY)	/FP (FRONT. + REAR.)					
ML75E	•	0	0	0						
ML 80E ML 100E	•	0	0	0	0					
ML 120EL	•			0						
ML 120E ML 140E	•	0	0	0	0					
ML 150E	•	0	0	0	0					
ML 160E	•	0	0	0						
ML 180E	•	0	0	0						
ML 110E & ML 150E 4x4		•	0							

- () Standard
- (o) Optionals







AFTER-SALES SERVICES

With Eurocargo, you can have all the assistance you need, thanks to the vast range of services tailored to your requirements, and IVECO's extensive geographical coverage. Your new vehicle shows total flexibility even at times of need, and will keep you going mile after mile, with absolute professionalism.



ELEMENTS

Assistance services tailored to suit every mission.

IVECO formulated ELEMENTS with one goal in mind: to provide every customer with service tailored to their needs. A wide range of planned maintenance contracts service schedules, devised to keep your vehicle in perfect shape at all times. ELEMENTS offers specialised, high-quality services designed to give EUROCARGO vehicles low running costs, long life and long-term value.



IVECO CAPITAL

IVECO CAPITAL, IVECO Group's in-house financial services arm, offers targeted solutions for the purchase, leasing and contract hire (including R&M) of every type of vehicle, whether new or used (including conversion). IVECO CAPITAL helps customers choose the financial product most suitable to their company's economic and fiscal profile.

IVECO CAPITAL services are available from all IVECO dealerships.



ASSISTANCE NON-STOP (ANS24)

One phone call and it's back to business. The IVECO CUSTOMER CENTER is available 24/7.

80 operators in 10 different languages, ready to activate the nearest IVECO point in order to get the vehicle back on the road as soon as possible.



An extensive, professional network for a constantly efficient vehicle.

IVECO workshops provide the manufacturer's quality combined with the skill of technicians who know your vehicle like no-one else. Specialised diagnostic and repair tools such as E.A.S.Y. and its accessories EasyScope & Easy Skite guarantee efficiency and rapidity even in indirect assistance missions (Teleservices).



ORIGIN 100% IVECO

The long-term excellence of Eurocargo's performance is assured by the use of **ORIGIN** 100% IVECO Original Parts, which are the fruit of painstaking selection of materials and suppliers, and specific, rigorous product testing.

The immense range of original products includes all **new parts** and a wide selection of remanufactured engines, gearboxes and components. Servicing kits designed to minimise TCO are also available with the new Euro6 range.

IVECO knows the value of your time. That's why it has an efficient, state-of-theart original parts sourcing and distribution system, which ensures integrated re-stocking of its authorised support network, with daily, round-the-clock deliveries, all over the world.



With the exclusive IVECO Accessory line, you can customise your Eurocargo to make it unique in terms of safety, technology and comfort.

EUROCARGO

EURO VI ENGINES AND PERFORMANCE



NEW TECTOR 5 AND 7 ENGINES



TOTAL COST OF OWNERSHIP AND EFFICIENCY



OPTIMISED FUEL-EFFICIENCY

ease of maintenance

RELIABILITY

PROVEN DRIVELINE
GEARBOXES: ZF MANUAL, EUROTRONIC
AUTOMATED AND ALLISON AUTOMATIC
IVECO AND MERITOR REAR AXLES

CUSTOMER SERVICES



ASSISTANCE NON-STOP 24/7
ELEMENTS TAILORED ASSISTANCE PROGRAMME
ORIGIN 100% IVECO PARTS IVECO CAPITAL FINANCE SERVICES

COMFORT



ERGONOMIC POSITIONING
OF INSTRUMENTS

COMPARTMENTS





OVER 11,000 PERMUTATIONS

3 CAB TYPES 2 ROOF HEIGHTS 13 TRANSMISSIONS 15 WHEELBASES

SAFETY



ACTIVE, PASSIVE AND PREVENTIVE SAFETY

ELECTRONIC SYSTEMS

7.5-10 TONNES = ABS AS STANDARD.

OPTIONAL ASR AND EVSC II-18 TONNES = EVSC AS STANDARD

DESIGN



ITALIAN STYLE AERODYNAMIC EFFICIENCY

















CONTENTS

- 2. EUROCARGO. PERFECT IN EVERY SITUATION
 - 4. EURO VI ENGINES AND PERFORMANCE
 - 10. VERSATILITY
 - 20. DESIGN
 - 24. COMFORT
 - 30. SAFETY
 - 32. RELIABILITY
 - 38. CUSTOMER SERVICES
 - 42. NEW EUROCARGO EURO VI
- 44. EUROCARGO: PERFECT IN EVERY SITUATION
 - 47. NEW EUROCARGO EURO VI COLOURS

TAKE A CLOSER LOOK AT THE WORLD OF IVECO ON: WWW.IVECO.COM





NEW EUROCARGO E5 COLOURS



50126 MARANELLO RED



50105 White



50174 GRENADA RED



50162 MINERAL GREY



50173 ALPINE WHITE



50177 ALSACE GREEN



50178 MARRAKESH YELLOW



50179 LYON BLUE



50180 CARRARA IVORY



50181 PRAGUE YELLOW



50182 ISTANBUL BLUE



52301 Desert Orange

+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ + 8582	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ Z	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ + PUBLICATION MI38582	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ S FOR ANY	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ CHANGES	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ TO MAKE	+
+	+	+	+	+	+	+	+		V/	= (30	0)	+	+	+	+	+	+	THE RIGHT.	+
+	+	+	+	+	+	+	+				O . C		+	+	+	+	+	+	+ ERVES TH	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ /ECO RES	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ (AMPLE. I'	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ 'AY OF EV	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+)ED BY W	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ + PROVIE	NOTICE.
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ OGUE AR	THOOUT +
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ IIS CATAL	× 1 IME
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ = = = = = = = = = = = = = = = = = = =	us at an +
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ CONTAIN	A REASOI +
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ IMAGES	COMMERCIAL OR CONSTRUCTION REASONS AT ANY TIME WITHOUT NOTICE. + + + + + + + + + + + + + + + + + + +
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ ON AND	+ +
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+ FORMATI	ERCIAL C
+	+	+	+	+	+	+	IVEC	O S.p.A.	- VIA PUC	GLIA, 35 -	10156 TC	rino - it	TALY	+	+	+	+	+	+ =====================================	00 + E
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+